



FABRICANTES DE
MOLINOS DE CAFÉ

MANUFACTURERS
OF COFFEE GRINDERS

Molino de café profesional
para todo tipo de cafés

Professional coffee grinder
for all types of coffee.

TRANQUILO II ABS

COLLECTION CLASSIC

TECHNICAL CHARACTERISTICS 0-500gr/6' Max 1Kg

Voltage: 230V / 220V / 110V

Frequency: 50Hz / 60Hz

Phases: 1(monophase)

RPM: 1.300 / 1.600

Current: 1.15A / 2,47A

Capacitor: 10nf / 40nf

Power: 0,10Hp / 270W

Protection rating: IP21

Motor supplied with thermal protector

Maximum operating time: 30 min.

Tempered steel grinding wheel (62HRC) ø 60mm

Lifespan of grinding wheels: 500kg

Hopper capacity: 1/2kg

Doser capacity: 300g

Doser regulation: 5/12g

Doser lever: right/left

Stop/start standard version: manual start

Dimensions width x length x height: 170x340x410mm


Weight: 6kg

Air noise: 77dB

Diseñado bajo directiva 89/392 CE.



Grinding blades in tempered steel
(62HRC) ø 60mm.



GREY

DARK GREY

BLACK

PURPLE



MAIN ATTRIBUTES

Hopper (1/2kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork manufactured in anti-scratch material, in a single piece (less vibrations, more robustness). With ventilation system (internal air inlet and outlet). Tray integrated into the bodywork. Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65HRC) 60mm in diameter.

Optional: Left- or right-handed doser lever. Coffee counter. Optional customisation system on the doser in chrome plate.

