



TECHNICAL SPECIFICATIONS

- * Made of stainless steel
- * Easy to reach controls and units thanks to the removable front panel
- * Safety thermostat
- * Signal lamps showing voltage and reached temperature
- * Stainless steel lid hinged and sprin-balanced in all opening positions
- * Indirect heating system with water cavity or steam circulation
- * Cavity pressure controlled by safety valve calibrated at 0.5 bar and pressure gauge with analogue reading
- * Heating elements shielded with Incoloy 800
- * It can be matched with other appliances by means of special joint elements
- * AISI 304 stainless steel cooking tanks, 2 to 4 mm thick
- * Prearranged for hot and cold water connection (D-F)
- * 3- positions switch and temperature arrangement thermostat

TECHNICAL SHEET

Power	kW	9
Frequency	Hz	50
Voltage	V	400 3N ~
Tank Capacity		50lt
Tank Dimensions	cm	Ø40xh45
Heating		Indiretto
Tank Type		AISI 316
Width	cm	70
Depth	cm	70
Height	cm	85
Packaging Width	cm	96,0
Packaging Depth	cm	87,0
Packaging Height	cm	115,0
Net Weight	kg	84,0000
Gross Weight	kg	104,0000
Volume	m³	0,9600



Information shown is provided only as a guide. The company reserves the right to modify these data without notifying anytime. La validità dei dati riportati è indicativa. L'Azienda si riserva il diritto di apportare, in qualsiasi momento, variazioni anche senza preavviso.