



ELECTRICAL PIZZA OVENS

- Stainless Steel Construction in front
- Italian-made claystones
- Independently controlled upper and bottom heating elements
- In-built indoor lights
- Optional oven stand
- Optional analog thermometer
- Temperatures reaching up to 400 Degrees Celcius



TECHNICAL SPECIFICATIONS

MODEL	PO 5050 DE	PO 5252 DE	PO 6262 DE	PO 6868 DE	PO 6292 DE	PO 9262 DE	PO 9292 DE
EXTERNAL MEASUREMENTS (x-y-z cm)	76 x 75,5 x 51	80 x 75 x 76	88 x 85 x 76	94 x 91,5 x 76	88 x 114,5 x 76	118 x 85 x 76	118 x 114,5 x 76
INTERNAL MEASUREMENTS (X-y-z cm)	50 x 50 x 10	52 x 52 x 15	62 x 62 x 15	68 x 68 x 15	62 x 92 x 15	92 x 62 x 15	92 x 92 x 15
TOTAL ELECTRIC POWER (KW)	6	8	10	11	12	12	16
ELECTRIC SUPPLY VOLTAGE (V)	230/400	230/400	380/400	380/400	380/400	380/400	380/400
OPERATING FREQUENCY (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60
THERMOSTAT INTERVAL (°C)	0-450	0-450	0-450	0-450	0-450	0-450	0-450
FEED WIRING mm (H07 RNF)	5x2,5	5x4	5x4	5x4	5x4	5x4	5x4
PROTECTION CLASS	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
NET WEIGHT (KG)	65	100	115	125	145	145	190
NOMINAL FLOW (A)	20	20	25	25	32	32	32
INSULATION	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL
CURING STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE
CAPASITY	4+4 Pieces Ø25 cm	4+4 Pieces Ø25 cm	4+4 Pieces Ø30 cm 5+5 Pieces Ø25 cm	4+4 Pieces Ø33 cm	6+6 Pieces Ø30 cm	6+6 Pieces Ø30 cm	9+9 Pieces Ø30 cm

TECHNICAL SPECIFICATIONS

MODEL	PO 5050-E	PO 6262-E	PO 6868-E	PO 6292-E	PO 9262-E	PO 9292-E
EXTERNAL MEASUREMENTS (x-y-z cm)	76 x 75,5 x 35	88 x 85 x 43	94 x 91,5 x 43	88 x 114 ,5 x 43	118 x 85 x 43	118 x 114,5 x 43
INTERNAL MEASUREMENTS (x-y-z cm)	50 x 50 x 10	62 x 62 x 15	68 x 68 x 15	62 x 92 x 15	92 x 62 x 15	92 x 92 x 15
TOTAL ELECTRIC POWER (KW)	4	5	5,5	6	6	8
ELECTRIC SUPPLY VOLTAGE (V)	230/400	230/400	230/400	380/400	380/400	380/400
OPERATING FREQUENCY (Hz)	50/60	50/60	50/60	50/60	50/60	50/60
THERMOSTAT INTERVAL (°C)	0-450	0-450	0-70	0-450	0-450	0-450
FEED WIRING mm (H07 RNF)	4x2,5	4x2,5	4x2,5	4x2,5	4x2,5	4x2,5
PROTECTION CLASS	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
NET WEIGHT (KG)	46	65	72	85	85	110
NOMINAL FLOW (A)	16	20/16	20/16	16	16	25
INSULATION	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL
CURING STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE
CAPASITY	4 Pieces Ø25 cm	4 Pieces Ø30 cm 5 Pieces Ø25 cm	4 Pieces Ø33 cm	6 Pieces Ø30 cm	6 Pieces Ø30 cm	9 Pieces Ø30 cm