



PRICELIST

BAKERLUX SHOP.Pro™

VALID FROM: 05-2020



LONGLife4!

FOR BAKERLUX SHOP.Pro™
MASTER AND TOUCH MODELS ONLY

The most solid demonstration of the quality and reliability of the BAKERLUX SHOP.Pro™.

You can extend your warranty* on spare parts for up to 4 years or 10,000 hours of use.

Activating the LONG.Life4 warranty is easy.

Simply connect your new BAKERLUX SHOP.Pro™ MASTER or TOUCH oven to the Internet via an Ethernet cable (LAN) or via Wi-Fi using their respective accessories and register it on the Unox website.

LAN kit Art.: XEC011

Wi-Fi kit Art.: XEC012

*(find out more at www.unox.com, conditions apply).





CAMILLA & VITTORIA 600x400



CAMILLA.MATIC

ELECTRIC LOCK
AUTOMATIC OPENING

10 TRAYS	MASTER	TOUCH	
Model	XEFT-10EU-EMRV	XEFT-10EU-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	400 V - 3N	400 V - 3N	
Electrical power	15,5 kW	15,5 kW	
Dimensions WxDxH (mm)	800x829x952	800x829x952	
Weight	96 kg	96 kg	

Increased pitch on lateral support: **CAMILLA** 8 trays 600x400 - 94 mm pitch. Art.: XUC154Left-to-right door opening: **XEFT-10EU-EMLV** / **XEFT-10EU-ETLV**.Version equipped with drain: **XEFT-10EU-EM*V-DR** / **XEFT-10EU-ET*V-DR**.

CAMILLA

MANUAL LOCK

10 TRAYS	TOUCH	LED	GO
Model	XEFT-10EU-ETRV-MT	XEFT-10EU-ELRV	XEFT-10EU-EGRN
Opening type	Right-to-left door opening	Right-to-left door opening	Right-to-left door opening
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	400 V - 3N	400 V - 3N	400 V - 3N
Electrical power	15,5 kW	15,5 kW	15,5 kW
Dimensions WxDxH (mm)	800x829x952	800x829x952	800x829x952
Weight	96 kg	96 kg	96 kg

Increased pitch on lateral support: **CAMILLA** 8 trays 600x400 - 94 mm pitch. Art.: XUC154Left-to-right door opening: **XEFT-10EU-ETLV-MT** / **XEFT-10EU-ELLV** / **XEFT-10EU-EGLN**.Version equipped with drain: **XEFT-10EU-ET*V-MT-DR** / **XEFT-10EU-EL*V-DR** / **XEFT-10EU-EG*N-DR**.

VITTORIA.MATIC

ELECTRIC LOCK
AUTOMATIC OPENING

6 TRAYS	MASTER	TOUCH	
Model	XEFT-06EU-EMRV	XEFT-06EU-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	400 V - 3N	400 V - 3N	
Electrical power	10,3 kW	10,3 kW	
Dimensions WxDxH (mm)	800x829x682	800x829x682	
Weight	72 kg	72 kg	


Increased pitch on lateral support: **VITTORIA** 5 trays 600x400 - 94 mm pitch. Art.: XUC153Left-to-right door opening: **XEFT-06EU-EMLV** / **XEFT-06EU-ETLV**.Version equipped with drain: **XEFT-06EU-EM*V-DR** / **XEFT-06EU-ET*V-DR**.

VITTORIA

MANUAL LOCK

6 TRAYS	TOUCH	LED	GO
Model	XEFT-06EU-ETRV-MT	XEFT-06EU-ELRV	XEFT-06EU-EGRN
Opening type	Right-to-left door opening	Right-to-left door opening	Right-to-left door opening
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	400 V - 3N	400 V - 3N	400 V - 3N
Electrical power	10,3 kW	10,3 kW	10,3 kW
Dimensions WxDxH (mm)	800x829x682	800x829x682	800x829x682
Weight	72 kg	72 kg	72 kg

Increased pitch on lateral support: **VITTORIA** 5 trays 600x400 - 94 mm pitch. Art.: XUC153Left-to-right door opening: **XEFT-06EU-ETLV-MT** / **XEFT-06EU-ELLV** / **XEFT-06EU-EGLN**.Version equipped with drain: **XEFT-06EU-ET*V-MT-DR** / **XEFT-06EU-EL*V-DR** / **XEFT-06EU-EG*N-DR**.

				MASTER	TOUCH	LED	GO					MASTER	TOUCH	LED	GO
				• Compatible	Not available										
	DECKTOP		DECK SHOP.Pro with integrated control 600x400 Single tray static oven Capacity: 1 600x400 - Voltage: 230 V- 1N - Frequency: 50 / 60 Hz - Electrical power: 2,7 kW - Dimensions: 800x840x405 WxDxH mm - Weight: 54,5 Kg Art.: XEKDT-01EU-D	•	•	•	-		DECK SHOP.Pro with integrated control 600x400 Single tray static oven with steam generator Capacity: 1 600x400 - Voltage: 230 V- 1N - Frequency: 50 / 60 Hz - Electrical power: 2,7 kW - Dimensions: 800x840x405 WxDxH mm - Weight: 60,5 Kg Art.: XEKDT-01EU-S	•	•	•	-		
	PROVERS		Prover with BOILER - Capacity: 8 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 2,3 kW - Max. temperature: 50°C - Dimensions: 800x792x750 WxDxH mm - Weight: 49 kg Art.: XEKPT-08EU-B Prover - Capacity: 8 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 1,2 kW - Max. temperature: 50°C - Dimensions: 800x792x750 WxDxH mm - Weight: 40 kg Art.: XEKPT-08EU-C	•	•	•	-		Prover with BOILER - Capacity: 10 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 2,3 kW - Max. temperature: 50°C - Dimensions: 800x792x886 WxDxH mm - Weight: 54 kg Art.: XEKPT-10EU-B Prover - Capacity: 10 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 1,2 kW - Max. temperature: 50°C - Dimensions: 800x792x886 WxDxH mm - Weight: 45 kg Art.: XEKPT-10EU-C	•	•	•	-		
STANDS & WHEELS		High Open stand with lateral supports Dimensions: 794x688x738 WxDxH mm - Pitch: 60 mm - Weight: 10 kg Art.: XEKRT-08EU-H	•	•	•	•			Intermediate open stand with lateral supports Dimensions: 794x688x559 WxDxH mm - Pitch: 60 mm - Weight: 7 kg Art.: XEKRT-06EU-M	•	•	•	•		
		Low positioning stand Dimensions: 794x688x355 WxDxH mm - Weight: 5,5 kg Art.: XWKRT-00EF-L	•	•	•	•			Floor positioning stand Dimensions: 794x688x150 WxDxH mm - Weight: 4 kg Art.: XWKRT-00EF-F	•	•	•	•		
		Wheels kit with safety chains For Models: XEKRT-/00/06/08/EU/EF-F/H/M - XEKPT-08EU-C - XEKPT-10EU-C. 4 wheels complete Kit: 2 wheelWls with brake 2 wheels without brake. H 110 mm Art.: XUC012	•	•	•	•		Feet kit 2 brakets h100 to place the oven on tables and have easy access to clean under the oven. Art.: XUC035	•	•	•	•			
		Feet kit for prover For prover positioning. Complete kit composed by 4 adjustable feet. Art.: XUC045	•	•	•	-									
HOODS		Ventless Hood Water connection required. Frequency: 50/60 Hz - Electrical power: 0,2 kW - Exhaust chimney diameter: 121 mm - Min. air flow: 550 m3/h - Max. air flow: 750 m3/h - Dimensions: 800x863x276 WxDxH mm - Weight: 23 kg Art.: XEKHT-HCEU	•	•	•	-		Waterless hood For Models: MASTER, TOUCH, LED Frequency: 50 / 60 Hz - Electrical power: 0,08 kW - Dimensions: 800x863x205 WxDxH mm - Weight: 25 Kg Art.: XEKHT-ACEU	•	•	•	-			
		Condenser It can be connected to a single oven. Voltage: 230 V- 1N - Frequency: 50 / 60 Hz - Weight: 7 Kg Art.: XEKCT-HCEH-M	•	•	•	•									
OTHER ACCESSORIES		Single unit installation kit - Contains water drain, fittings, piping U-trap, connections and 1 SPRAY&Rinse bottle (750ML). Art.: XUC013	•	•	•	•		Shower Cleaning kit - Contains water drain, fittings, piping U-trap, connections, anti drip door trays, shower kit and 1 bottle of SPRAY&Rinse (750ML). Art.: XHC027	•	•	•	•			
		Double stack installation kit Contains steel components, water drain and all the necessary fittings to install double-stack ovens. XWKQT-00EF-E	•	•	•	•		Double stack installation kit Contains steel components, water drain and all the necessary fittings to install double-stack ovens. To be used when an XEFT-04EU-*unit is at the bottom. Art.: XWKQT-04EF-E	•	•	•	•			
		Water tank kit for oven/s placed on a table It requires the purchase of Art.XHC016 pump kit Art.: XHC021	•	•	•	-		Water tank kit for oven/s placed on a stand It requires the purchase of Art.XHC016 pump kit Art.: XHC023	•	•	•	-			
		Water tank kit for oven placed on a prover It requires the installation of XUC012 or XUC045 Art.: XHC024	•	•	•	-		Water tank to be placed on top of the oven. Suitable only for pump version ovens or combined with the pump kit XHC016 Art.: XHC026	•	•	•	-			
		Buzzer kit It allows to increase the ring's intensity produced by the oven to inform you about the end of the baking. Art.: XEC015	•	•	•	•		Pump kit Necessary if no direct water supply is available. In case of MAXI.Link solution, one kit per each oven and/or prover is required Art.: XHC016	•	•	•	-			
RECOMMENDED INSTALLATION TOOLS	WATER TREATMENT		UNOX.Pure Permits to treat up to 7000 litres of water (depending on the water temporary hardness) Art.: XHC003	•	•	•	-		Refill UNOX.Pure filtering system Art.:XHC004	•	•	•	-		
	INTERNET CONNECTION		INTERNET CONNECTION To maintain the UNOX LONG.Life4 extended warranty on spare parts up to 4 years or 10000 running hours, your UNOX oven must be connected to the internet.BAKERLUX SHOP.Pro™ ovens can be connected by Ethernet cable or WIFI connection.					LAN kit Art.: XEC011	•	•	-	-			
								Wi-Fi kit Art.: XEC012	•	•	-	-			

ROSSELLA & ELENA 600x400



ROSSELLA.MATIC
ELECTRIC LOCK
AUTOMATIC OPENING

4 TRAYS	MASTER	TOUCH	
Model	XEFT-04EU-EMRV	XEFT-04EU-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	400 V - 3N	400 V - 3N	
Electrical power	6,9 kW	6,9 kW	
Dimensions WxDxH (mm)	800x811x502	800x811x502	
Weight	57 kg	57 kg	

Increased pitch on lateral support: **ROSSELLA** 3 trays 600x400 - 100 mm pitch. Art.: XUC152

Left-to-right door opening: **XEFT-04EU-EMLV** / **XEFT-04EU-ETLV**.

Version equipped with drain: **XEFT-04EU-EM*V-DR** / **XEFT-04EU-ET*V-DR**.



ROSSELLA
MANUAL LOCK

4 TRAYS	TOUCH	LED	GO
Model	XEFT-04EU-ETDV	XEFT-04EU-ELDV	XEFT-04EU-EGDN
Opening type	Up-to-down	Up-to-down	Up-to-down
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	400 V - 3N	400 V - 3N	400 V - 3N
Electrical power	6,9 kW	6,9 kW	6,9 kW
Dimensions WxDxH (mm)	800x811x500	800x811x500	800x811x500
Weight	57 kg	57 kg	57 kg

Increased pitch on lateral support: **ROSSELLA** 3 trays 600x400 - 100 mm pitch. Art.: XUC152

Version equipped with drain: **XEFT-04EU-ETDV-DR** / **XEFT-04EU-ELDV-DR** / **XEFT-04EU-EGDN-DR**.



ELENA.MATIC
ELECTRIC LOCK
AUTOMATIC OPENING


3 TRAYS	MASTER	TOUCH	
Model	XEFT-03EU-EMRV	XEFT-03EU-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	230 V - 1N	230 V - 1N	
Electrical power	3,5 kW	3,5 kW	
Dimensions WxDxH (mm)	800x811x427	800x811x427	
Weight	46 kg	46 kg	

Left-to-right door opening: **XEFT-03EU-EMLV** / **XEFT-03EU-ETLV**.



ELENA
MANUAL LOCK

3 TRAYS	TOUCH	LED	GO
Model	XEFT-03EU-ETDV	XEFT-03EU-ELDV	XEFT-03EU-EGDN
Opening type	Up-to-down	Up-to-down	Up-to-down
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	230 V - 1N	230 V - 1N	230 V - 1N
Electrical power	3,5 kW	3,5 kW	3,5 kW
Dimensions WxDxH (mm)	800x811x425	800x811x425	800x811x425
Weight	46 kg	46 kg	46 kg

● Compatible - Not available			MASTER	TOUCH	LED	GO				MASTER	TOUCH	LED	GO
	DECKTOP	 DECK SHOP.Pro with integrated control 600x400 Single tray static oven Capacity: 1600x400 - Voltage: 230 V- 1N - Frequency: 50 / 60 Hz - Electrical power: 2,7 kW - Dimensions: 800x840x405 WxDxH mm - Weight: 54,5 Kg Art.: XEKDT-01EU-D	●	●	●	-	 DECK SHOP.Pro with integrated control 600x400 Single tray static oven with steam generator Capacity: 1600x400 - Voltage: 230 V- 1N - Frequency: 50 / 60 Hz - Electrical power: 2,7 kW - Dimensions: 800x840x405 WxDxH mm - Weight: 60,5 Kg Art.: XEKDT-01EU-S	●	●	●	-		
	PROVERS	 Prover with BOILER - Capacity: 8 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 2,3 kW - Max. temperature: 50°C - Dimensions: 800x792x750 WxDxH mm - Weight: 49 kg Art.: XEKPT-08EU-B Prover - Capacity: 8 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 1,2 kW - Max. temperature: 50°C - Dimensions: 800x792x750 WxDxH mm - Weight: 40 kg Art.: XEKPT-08EU-C	●	●	●	-	 Prover with BOILER - Capacity: 10 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 2,3 kW - Max. temperature: 50°C - Dimensions: 800x792x886 WxDxH mm - Weight: 54 kg Art.: XEKPT-10EU-B Prover - Capacity: 10 trays 600x400 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 1,2 kW - Max. temperature: 50°C - Dimensions: 800x792x886 WxDxH mm - Weight: 45 kg Art.: XEKPT-10EU-C	●	●	●	-		
STANDS & WHEELS	 High Open stand with lateral supports Dimensions: 794x688x738 WxDxH mm Pitch: 60 mm - Weight: 10 kg Art.: XEKRT-08EU-H	●	●	●	●	 Intermediate open stand with lateral supports Dimensions: 794x688x559 WxDxH mm Pitch: 60 mm - Weight: 7 kg Art.: XEKRT-06EU-M	●	●	●	●			
	 Low positioning stand Dimensions: 794x688x355 WxDxH mm - Weight: 5,5 kg Art.: XWKRT-00EF-L	●	●	●	●	 Floor positioning stand Dimensions: 794x688x150 WxDxH mm - Weight: 4 kg Art.: XWKRT-00EF-F	●	●	●	●			
	 Wheels kit with safety chains - For Models: XEKRT-/00/06/08/EU/EF-F/H/M - XEKPT-08EU-C - XEKPT-10EU-C. 4 wheels complete Kit: 2 wheels with brake 2 wheels without brake. H 110 mm Art.: XUC012	●	●	●	●	 Feet kit 2 brakets h100 to place the oven on tables and have easy access to clean under the oven. Art.: XUC035	●	●	●	●			
	 Feet kit for prover For prover positioning. Complete kit composed by 4 adjustable feet. Art.: XUC045	●	●	●	-								
HOODS	 Ventless Hood Water connection required. Frequency: 50/60 Hz - Electrical power: 0,2 kW - Exhaust chimney diameter: 121 mm - Min. air flow: 550 m3/h - Max. air flow: 750 m3/h - Dimensions: 800x863x276 WxDxH mm - Weight: 23 kg Art.: XEKHT-HCEU	●	●	●	-	 Waterless hood For Models: MASTER, TOUCH, LED Frequency: 50 / 60 Hz - Electrical power: 0,08 kW Dimensions: 800x863x205 WxDxH mm Weight: 25 Kg Art.: XEKHT-ACEU	●	●	●	-			
	 Condenser. It can be connected to a single oven. Voltage: 230 V- 1N - Frequency: 50 / 60 Hz -Weight: 7 Kg Art.: XEKCT-HCEH-M	●	●	●	●	 Shower Cleaning kit - Contains water drain, fittings, piping U-trap, connections, anti drip door trays, shower kit and 1 bottle of SPRAY&Rinse (750ML). Art.: XHC027							
OTHER ACCESSORIES	 Double stack installation kit Contains steel components, water drain and all the necessary fittings to install double-stack ovens. XWKQT-00EF-E	●	●	●	●	 Double stack installation kit Contains steel components, water drain and all the necessary fittings to install double-stack ovens. To be used when an XEFT-04EU-*unit is at the bottom. Art.: XWKQT-04EF-E	●	●	●	●			
	 Water tank kit for oven/s placed on a table It requires the purchase of Art.XHC016 pump kit Art.: XHC021	●	●	●	-	 Water tank kit for oven/s placed on a stand It requires the purchase of Art.XHC016 pump kit Art.: XHC023	●	●	●	-			
	 Water tank kit for oven placed on a prover It requires the installation of XUC012 or XUC045 Art.: XHC024	●	●	●	-	 Water tank to be placed on top of the oven. Suitable only for pump version ovens or combined with the pump kit XHC016 Art.: XHC026	●	●	●	-			
	 Buzzer kit - It allows to increase the ring's intensity produced by the oven to inform you about the end of the baking. Art.: XEC015	●	●	●	●	 Pump kit - Necessary if no direct water supply is available. In case of MAXi.Link solution, one kit per each oven and/or prover is required Art.: XHC016	●	●	●	-			
RECOMMENDED INSTALLATION TOOLS	WATER TREATMENT	 Bakery.Pure filtering system Permits to treat up to 1000 litres of water (depending on the water temporary hardness) Art.: XHC010	●	●	●	-	 Refill Bakery.Pure filtering system Art.: XHC011	●	●	●	-		
	INTERNET CONNECTION	 INTERNET CONNECTION To maintain the UNOX LONG.Life4 extended warranty on spare parts up to 4 years or 10000 running hours, your UNOX oven must be connected to the internet. BAKERLUX SHOP.Pro™ ovens can be connected by Ethernet cable or WIFI connection.					LAN kit Art.: XEC011	●	●	-	-		
						Wi-Fi kit Art.: XEC012	●	●	-	-			

ARIANNA & STEFANIA 460x330



ARIANNA.MATIC

ELECTRIC LOCK
AUTOMATIC OPENING

4 TRAYS	MASTER	TOUCH	
Model	XEFT-04HS-EMRV	XEFT-04HS-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	230 V- 1N	230 V- 1N	
Electrical power	3,5 kW	3,5 kW	
Dimensions WxDxH (mm)	600x669x502	600x669x502	
Weight	39 kg	39 kg	

4 trays TG 305 included. Increased pitch on lateral support: **ARIANNA** 3 trays 460x330 - 100 mm pitch. Art.: XUC151
Left-to-right door opening: **XEFT-04HS-EMLV** / **XEFT-04HS-ETLV**.



ARIANNA

MANUAL LOCK

4 TRAYS	TOUCH	LED	GO
Model	XEFT-04HS-ETDV	XEFT-04HS-ELDV	XEFT-04HS-EGDN
Opening type	Up-to-down	Up-to-down	Up-to-down
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	230 V- 1N	230 V- 1N	230 V- 1N
Electrical power	3,5 kW	3,5 kW	3,5 kW
Dimensions WxDxH (mm)	600x669x500	600x669x500	600x669x500
Weight	39 kg	39 kg	39 kg

4 trays TG 305 included. Increased pitch on lateral support: **ARIANNA** 3 trays 460x330 - 100 mm pitch. Art.: XUC151
Versions with pump (Only TOUCH and LED versions): **XEFT-04HS-ETDP** / **XEFT-04HS-ELDP**.



STEFANIA.MATIC

ELECTRIC LOCK
AUTOMATIC OPENING

3 TRAYS	MASTER	TOUCH	
Model	XEFT-03HS-EMRV	XEFT-03HS-ETRV	
Opening type	Right-to-left door opening	Right-to-left door opening	
Type of lock	Electric lock - automatic opening	Electric lock - automatic opening	
Pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	230 V- 1N	230 V- 1N	
Electrical power	3 kW	3 kW	
Dimensions WxDxH (mm)	600x669x427	600x669x427	
Weight	36 kg	36 kg	

3 trays TG 305 included.
Left-to-right door opening: **XEFT-03HS-EMLV** / **XEFT-03HS-ETLV**.





STEFANIA

MANUAL LOCK

3 TRAYS	TOUCH	LED	GO
Model	XEFT-03HS-ETDV	XEFT-03HS-ELDV	XEFT-03HS-EGDN
Opening type	Up-to-down	Up-to-down	Up-to-down
Type of lock	Manual lock	Manual lock	Manual lock
Pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	230 V- 1N	230 V- 1N	230 V- 1N
Electrical power	3 kW	3 kW	3 kW
Dimensions WxDxH (mm)	600x669x425	600x669x425	600x669x425
Weight	36 kg	36 kg	36 kg

3 trays TG 305 included.
Versions with pump (Only TOUCH and LED versions): **XEFT-03HS-ETDP** / **XEFT-03HS-ELDP**.

● Compatible - Not available			MASTER TOUCH LED GO	MASTER TOUCH LED GO		
RECOMMENDED INSTALLATION TOOLS	PROVERS	 Prover Capacity: 8 trays 460x330 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 1,2 kW - Max. temperature: 50°C - Dimensions: 600x711x750 WxDxH mm - Weight: 26 kg Art.: XEKPT-08HS-C	● ● ● -	 Prover with BOILER Capacity: 8 trays 460x330 - Pitch: 70 mm - Voltage: 220-240V-1PH+N+PE - Frequency: 50 / 60 Hz - Electrical power: 2,3 kW - Max. temperature: 50°C - Dimensions: 600x711x750 WxDxH mm - Weight: 35 kg Art.: XEKPT-08HS-B		
		STANDS & WHEELS	 High Open stand with lateral supports Dimensions: 594X546X738 WxDxH mm Pitch: 60 mm - Weight: 9 kg Art.: XWKRT-08HS-H	● ● ● ●	 Intermediate open stand with lateral supports Dimensions: 594X546X559 WxDxH mm Pitch: 60 mm - Weight: 6 kg Art.: XWKRT-06HS-M	● ● ● ●
			 Floor positioning stand Dimensions: 594X546X150 WxDxH mm Weight: 3 kg Art.: XWKRT-00HS-F	● ● ● ●	 Wheels kit with safety chains For Models: XWKRT-06/08/HS-F/H/M - XEKPT-08EU-C - XEKPT-10EU-C. 4 wheels complete Kit: 2 wheels with brake 2 wheels without brake. H 110 mm Art.: XUC012	● ● ● ●
			 Feet kit 2 brakets h100 to place the oven on tables and have easy access to clean under the oven. Art.: XUC025	● ● ● ●	 Feet kit for prover For prover positioning. Complete kit composed by 4 adjustable feet. Art.: XUC045	● ● ● -
	HOODS	 Ventless Hood Water connection required. Frequency: 50 / 60 Hz - Electrical power: 0,2 kW - Exhaust chimney diameter: 121 mm - Min. air flow: 550 m³/h - Max. air flow: 750 m³/h - Dimensions: 600x731x276 WxDxH mm - Weight: 21 Kg Art.: XEKHT-HCHS	● ● ● -	 Waterless hood Frequency: 50 / 60 Hz - Electrical power: 0,105 kW - Dimensions: 600x731x205 WxDxH mm - Weight: 15 Kg Art.: XEKHT-ACHS	● ● ● ●	
		 Built-in installation kit Hood with activated carbon filter. Only compatible with ARIANNA models. Dimensions: 600x697x100 WxDxH mm - Weight: 8,5 Kg Art.: XWKHT-BCHS	● ● ● ●	 Condenser It can be connected to a single oven. Voltage: 230 V- 1N - Frequency: 50 / 60 Hz Weight: 7 Kg Art.: XEKCT-HCEH-M	● ● ● ●	
	OTHER ACCESSORIES	 Double stack installation kit Contains steel components, water drain and all the necessary fittings to install double-stack ovens. XWKQT-00HS-E	● ● ● ●			
		 Water tank kit for oven/s placed on a table It requires the purchase of Art.XHC016 pump kit Art.: XHC020	● ● ● -	 Water tank kit for oven/s placed on a stand It requires the purchase of Art.XHC016 pump kit Art.: XHC022	● ● ● -	
		 Water tank kit for oven placed on a prover It requires the installation of XUC012 or XUC045 Art.: XHC024	● ● ● -	 Water tank to be placed on top of the oven. Suitable only for pump version ovens or combined with the pump kit XHC016 Art.: XHC026	● ● ● -	
		 Buzzer kit It allows to increase the ring's intensity produced by the oven to inform you about the end of the baking. Art.: XEC015	● ● ● ●	 Pump kit Necessary if no direct water supply is available. In case of MAXI.Link solution, one kit per each oven and/or prover is required Art.: XHC016	● ● ● -	
	WATER TREATMENT	 Bakery.Pure filtering system Permits to treat up to 1000 litres of water (depending on the water temporary hardness) Art.: XHC010	● ● ● -	 Refill Bakery.Pure filtering system Art.: XHC011	● ● ● -	
		INTERNET CONNECTION	 INTERNET CONNECTION To maintain the UNOX LONG.Life4 extended warranty on spare parts up to 4 years or 10000 running hours, your UNOX oven must be connected to the internet. BAKERLUX SHOP.Pro™ ovens can be connected by Ethernet cable or WIFI connection.	LAN kit		Art.: XEC011
	Wi-Fi kit			Art.: XEC012	● ● - -	

BAKING ESSENTIALS

**FORO.BAKE**

Perforated aluminium pan for pastry and bakery products;
h 15 mm.
Can only be ordered in multiples of 2 pieces.

600x400**Art.: TG410****460x330****Art.: TG310****FORO.BLACK**

Non-stick perforated aluminium pan for pastry and bakery products; h 15 mm.
Can only be ordered in multiples of 2 pieces.

600x400**Art.: TG430****460x330****Art.: TG330****FAKIRO™**


Aluminium plate with 2 sides: flat side to bake, toast and regenerate pizza, focaccia and bread. Ribbed side to bake, toast and regenerate frozen pizza and focaccia. The ribbed side allows to evacuate the extra humidity produced during the defrosting process; h 13 mm.

600x400**Art.: TG440****460x330****Art.: TG335****FAKIRO.GRILL**

Non stick aluminium plate with 2 sides: flat side to bake, toast and fresh pizza, focaccia and bread. Ribbed side to bake, toast and regenerate frozen pizza and focaccia. The non-stick coating prevent burnt food stick on the tray. The ribbed side allows to evacuate the extra humidity produced during the defrosting process; h 13 mm.

600x400**Art.: TG465**

-



PATENTED

BAGUETTE.GRID

Chromium grid for pre-cooked baguettes or midi-baguettes. The light structure permits huge amount of heat and air on the food for a quicker baking process;
GRP410: h 27 mm - GRP310: h 32 mm.

600x400**Art.: GRP410****460x330****Art.: GRP310****FORO.BAGUETTE**

5 channels aluminium tray for pre-cooked frozen baguettes or midi-baguettes;
h 34 mm.

600x400**Art.: TG445**

-

**FORO.BAGUETTE.BLACK**

5 channels non-stick aluminium tray for fresh baguettes or midi-baguettes;
h 24 mm.

600x400**Art.: TG435**

-

**BAKE.BLACK**

Non-stick aluminium tray;
h 15,5 mm.
Can only be ordered in multiples of 2 pieces.

600x400**Art.: TG460**

-

**BAKE**

Aluminium pan;
TG305: h 11 mm - TG405: h 15 mm.
Can only be ordered in multiples of 2 pieces.

600x400**Art.: TG405****460x330****Art.: TG305****STEEL BAKE**

Stainless steel pan; h 20 mm.

600x400**Art.: TG450**

-

**PAN.FRY**

Enameled pan;
h 20 mm.

-

460x330**Art.: TG350****STEAM&FRY**

Stainless steel grid for steaming and French fries;
h 30 mm.

-

600x400**Art.: GRP420****STEAM**

Stainless steel grid for steaming;
h 30 mm.

-

460x330**Art.: GRP350****CHROMO.GRID**

Flat chromium plated wire grid,
h 8,5 mm.

-

600x400**Art.: GRP405****460x330****Art.: GRP305****FORO.SILICO**

Silicone coated perforated aluminium pan for pastry and bakery products;
TG415: h 9 mm
TG315: h 10 mm.

600x400**Art.: TG415****460x330****Art.: TG315****BAKE.SILICO**

Silicon aluminium tray;
h 9 mm

-

600x400**Art.: TG416**

ACCESSORIES FOR TRAYS

**Trays Trolley**

Capacity: 18 400x600
Pitch: 80 mm
Dimensions: 526x695x1700 WxDxH mm
Weight: 15 Kg

400x600**Art.: XTB0003****Trays Trolley**

Capacity: 18 600x400
Pitch: 80 mm
Dimensions: 726x495x1701 WxDxH mm
Weight: 15 Kg

600x400**Art.: XTB0005**

CLEANING AGENT

**SPRAY&Rinse**

Spray detergent for BAKERLUX SHOP.Pro™ ovens. One box contains n° 12 x 750 ml spray bottles. Trash the bottle once you have used the product.

Art.: DB1044

Single box purchase

Multiple box purchase: 6 boxes, unit cost

Multiple box purchase: 30 boxes (full pallet), unit cost

FEATURES

	● Standard	○ Optional	— Not available	MASTER	TOUCH	LED	CO
COOKING METHODS							
Convection baking with adjustable temperature (30°C-260°C)	●	●	●	●			
Convection baking with humidity and adjustable temperature (30°C-260°C)	●	●	●	—			
Maximum preheating temperature 260°C	●	●	●	●			
AUTOMATIC AND ADVANCE PROGRAMMING							
Cooking steps	9	9	3	3			
QUICK PROGRAMS:	—	—	12	12			
PROGRAMS:	896	99	99	99			
PROGRAMS: names and pictures can be assigned to saved programmes	●	●	—	—			
PROGRAMS: recipes can be saved with a name	●	●	—	—			
MULTI.Time: it manages more than 10 timers to control different products being cooked simultaneously	●	—	—	—			
UNOX INTELLIGENT.PERFORMANCE TECHNOLOGIES							
ADAPTIVE.Cooking™ technology: bake a single tray or a full load with the same baking program and get the exact same results.	●	—	—	—			
AUTO.Soft technology: controls the temperature to ensure total uniformity	●	—	—	—			
SMART.Preheating technology: the oven preheats to the desired temperature, taking into account its recent use	●	—	—	—			
AUTO.MATIC: automatic door opening, interrupting the baking process at just the right moment to guarantee excellent results.	●	●	—	—			
UNOX INTENSIVE.COOKING TECHNOLOGIES							
AIR.Plus technology: 2 speeds of air flow in the chamber, can be adjusted by user	●	●	●	—			
AIR.Plus technology: multiple fans running in reverse	●	●	●	●			
STEAM.Plus technology: mixed convection - humidity baking (20-40-60-100%)	●	●	●	—			
DRY.Plus technology: It extracts humidity from the baking chamber	●	●	●	●			
EFFICIENT.Power™: 300 seconds to go from 60 to 260°C.	●	●	●	●			
EFFICIENT.Power™: ENERGY STAR certification	●	●	●	●			
DATA DRIVEN COOKING TECHNOLOGIES							
Ethernet connection board to keep the oven connected to ddc.unox.com and UNOX App	○	○	—	—			
DDC Stats: Oven usage and consumption reports.	●	—	—	—			
BAKING STATIONS							
MAXI.LINK technology: It allows you to create units with two stacked ovens	●	●	●	—			
THERMAL INSULATION AND SAFETY							
Protek.SAFE™ technology: maximum thermal efficiency and working safety	●	●	●	●			
Protek.SAFE™ technology: the motor stops when the door is opened to limit energy loss	●	●	●	●			
DOOR OPENING							
Manual vertically-opening door (up to down) (Only for CAMILLA and VITTORIA models)	—	●	●	●			
Electromechanical and automatic horizontally-opening door (right-to-left; only for Matic versions)	●	●	—	—			
Manual horizontally-opening door (right-to-left)	—	—	●	●			
AUXILIARY FUNCTIONS							
Preheating temperatures up to 260°C that can be set by the user for each programme	●	●	●	●			
It shows the remaining time for the baking programme currently in use	●	●	●	●			
‘INFINITE’ continuous operation	●	●	●	●			
It shows the nominal and actual baking time, chamber temperature, humidity level and fan speeds	●	●	●	●			
Temperature units shown in °C or °F	●	●	●	●			
TECHNICAL DETAILS							
Tray supports in L-shaped sheet metal (Only for CAMILLA and VITTORIA models)	●	●	●	●			
Tray supports in chrome-plated steel (Only for ELENA and ROSSELLA models)	●	●	●	●			
Tray supports in chrome-plated steel with anti-tipping system (Only for STEFANIA and ARIANNA models)	●	●	●	●			
Sealed control panel to avoid steam infiltrating the circuit board (IPX4)	●	●	●	●			
Lightweight - Heavy Duty structure using innovative materials	●	●	●	●			
Door open switch	●	●	—	—			
Temperature limiter for safety	●	●	●	●			
Easy-to-clean, openable internal glass panel (only for right-to-left door opening models)	●	●	●	●			
Easy-to-clean internal glass panel (only for drop down opening models)	—	●	●	●			