



FABRICANTES DE  
MOLINOS DE CAFÉ

MANUFACTURERS  
OF COFFEE GRINDERS

Molino de café profesional  
para todo tipo de cafés

Professional coffee grinder  
for all types of coffee.

# TRANQUILO-TRON ABS

COLLECTION ON DEMAND

## TECHNICAL CHARACTERISTICS 0-500gr/6' Max 1Kg

VOLTAGE: 230V / 220V / 110V

FREQUENCY: 50Hz / 60Hz

PHASES: 1 (monophasic)

RPM: 1.300 / 1.600

CURRENT: 1,4A / 3A

CAPACITOR: 12nf / 40nf

POWER: 0,12Hp / 275W

PROTECTION RATING: IP21

MOTOR SUPPLIED WITH THERMAL PROTECTOR

MAXIMUM OPERATING TIME: 30min

TEMPERED STEEL GRINDING WHEELS (62HRc) ø 60mm

LIFESPAN OF GRINDING WHEELS: 500 Kg

HOPPER CAPACITY: 1/2Kg (OPTIONAL 1Kg)

MULTI-LANGUAGE TOUCH SCREEN

SELECTION FOR 1 OR 2 FRESHLY GROUND COFFEES OR CONTINUOUS GRINDING

TOTAL OR PARTIAL COFFEE COUNTER

ASSISTANT TIMER GRINDING POINT

DIMENSIONS WIDTH X LENGTH X HEIGHT: 170X340X410mm



WEIGHT: 8Kg

AIR NOISE: 77dB


Diseñado bajo directiva 89/392 CE.




Grinding blades in tempered steel  
(62HRc) ø 60mm.




GREY



DARK GREY



BLACK



PURPLE



### MAIN ATTRIBUTES

Hopper (1/2kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Body made of anti-scratch material, in a single piece (less vibrations, more robustness) with ventilation (internal air inlet and outlet) system. Tray integrated into the bodywork. – Touch screen for easy programming and use (Language selection – Setting the grinding program for each dose – Selection of 1 dose, 2 doses or continuous grinding – Coffee counter: total or partial consumption). Hardened steel grinding blades (62/65HRc) 60mm in diameter.

**Optional: Customisation system on the funnel in chrome plate.**

