

LA GAMMA LILLIPUT

The Lilliput Series - La Gamme Lilliput - La Gama Lilliput



LILLIPUT 4



LILLIPUT 6



LILLIPUT 10

TOP*	DIM. AxBxH cm	PESO WEIGHT / PESO Kg.
LILLIPUT /TP	98x105x23	20

* Top dotato di raccordo per camino a tiraggio naturale (aspiratore da 400 m³/h oppure 600m³/h a richiesta) / Top equipped with fitting for natural draft-chimney (400 m³/h or 600m³/h exhauster on demand) / Hotte avec cheminée à tirage naturel (Aspirateur 400 m³/h ou 600m³/h sur demande) / Top dotato de union para el tiro natural de la chimenea (Aspirador 400 m³/h o 600m³/h a pedido)

MOD. DI COTTURA BAKING UNITS/UNITÉ DE CUISSON/MÓD. DE COCCIÓN	DIM. EXT. AxBxH cm	TEMP. MAX. °C	n° TEGLIE TRAYS CAPACITY	PASSO TEGLIE DIST.BETWEEN TRAYS cm	PESO WEIGHT Kg	CONSUMO Max Medio CONSUMP. Max Average Kw	
LILLIPUT 4/MC	98x95x74	270 °C	4 (60x40)	8	93	8,3	4,1
LILLIPUT 6/MC	98x95x88	270 °C	6 (60x40)	8	117	10	5
LILLIPUT 10/MC	98x95x120	270 °C	10 (60x40)	8	158	15	7,5

CELLA DI LIEVITAZIONE PROOFING CABINET/ÉTUVE DE FERMENTATION/CÁMARA DE FERMENTACIÓN	DIM. AxBxH cm	n° TEGLIE TRAYS CAPACITY/N. PLATEAUX/N. BANDEJAS	PASSO TEGLIE cm	PESO WEIGHT/POIDS GEWICHT/PESO Kg.	POTENZA POWER/PUISSANCE LEISTUNG/POTENCIA Kw
LILLIPUT 4-6/CL	98x95x100	9	7,5	87	1
LILLIPUT 10/CL	98x95x70	5	7,5	70	1

BASAMENTI BASES/BASES	DIM. AxBxH cm	PESO WEIGHT / PESO Kg.
LILLIPUT 4-6/BM	98x85x100	49
LILLIPUT 10/BM	98x85x70	44