

“Heat is the secret ingredient.”
Harold McGee



The °Control Freak™ induction cooking system is the first of its kind to accurately measure, set and hold 221 cooking temperatures from 30°–250°C. The unique real-time sensing system uses a through-glass sensor to directly measure surface temperature. Probe Control™ remote thermometer to precisely control the temperature of both water and fat-based liquids.

The Intensity function gives incredible control over the heat up speed to the set temperature. Create function stores frequently used custom temperature profiles for simple one-touch recall.

Brought to you by Sage | PolyScience coming together to bring great design and unparalleled precision to the culinary world.

Visit www.sagepolyscience.com to learn about the entire line of PolyScience products and great recipe ideas.

Temperature Controlled Induction Cooking System

Technical Specifications	
PERFORMANCE	
Performance Range	30–250°C / 86–482°F
Dual NTC Probe Resolution	0–300°C / 32–572°F
Temperature Stability	±1°C / ±1.8°F
Power Range	100–2400 Watts
OPERATION	
Control Functionality	221 (in °C) / 397 (in °F) Possible Holding Temperatures
Timer	72 hr with “Repeat, Continue, Keep Warm and Stop Cooking” functions
WEIGHTS & DIMENSIONS	
Unit Dimensions (H x W x D)	110 x 350 x 470mm / 4.3 x 13.7 x 18.5in
Shipping Dimensions	487 x 288 x 618mm / 19.2 x 11.3 x 24.3in
Shipping Weight	11.2 kg / 24.7 lb
Agency Certification	UL/IEC Commercial Certification NSF Commercial Certification IPX3 Rated Water Protection
220–240V–50 / 2400 W	GMC850 BSS 2G UKI
ACCESSORIES	
Temperature Probe with Pot Clip Protective Travel and Storage Case USB Flash Drive	
Sold separately: Long Probe (Shift 250mm) with Pot Clip	

PRECISION INDUCTION HOB	Heat intensity control Dual fan cooling system Durable stainless steel housing High-heat resistant ceramic glass Tritan™ Polymer LCD display Color TFT screen USB port allows for software updates Easy clean housing Control knobs are removable and dishwasher safe
-------------------------	---